



Color: **White**

Panel: **ADVANCED**

- **Inverter technology** for energy savings and reduced noise levels
- Temperature stability of **±0.1 °C**
- Internal temperature uniformity of **±0.5 °C**
- Touch control panel with 7" display and password with 3 levels of access
- Data download to USB
- Backup battery for managing alarms in case of power failure
- Audible and visual alarms
- Wi-Fi connection (upon request)

## TECHNICAL FEATURES

Product Code	ASC701T
Temperature	+2°C / +50°C
Refrigeration Type	Forced air
Condensate Evaporation	Automatic
Refrigerant Gas	R290
Climatic Class	+16°C / +38°C (ST)
Gross Capacity (liters)	300
Net Capacity (liters)	270
External Dimensions (W x D x H mm)	600 x 650 x 1620

## ELECTRICAL DATA

Power Supply (V/ph/Hz)	220-230/1/50
Power Plug	Type F

## STRUCTURAL FEATURES

Structure	Upright
External Material	Anti-bacterial coated steel white colour
Internal Material	Stainless steel 18/10 AISI 304
Insulation Thickness (mm)	50
Insulated Door	Yes
Door Reversibility	Yes
Automatic Door Closure	Yes
Shelves Number	2
Shelf Material	Wire steel with white colour plastic coating
Shelves Dimensions (W x D mm)	460 x 470
Shelf Adjustment Step	7
Shelf Adjustment Step Range (mm)	100
Maximum Shelf Quantity	7
Drawers with extractable slides	Optional
Drawer Adjustment Step	7
Drawer Adjustment Step Range (mm)	100
Maximum Drawer Quantity	7
Unidirectional Rollers	4

## CONTROL PANEL

Display Type	Touch 7"
Languages	ITA - ENG - FRA

## CONTROL PANEL

Access Password	Yes
3-Level Access Password	Yes
Temperature Graph	Visible on display
Probe Type	PT1000
Alarm Signaling	Acoustic and visual
Alarm Indications	Text form
Adjustable High/Low Temperature Alarm	Yes
Adjustable Door Open Alarm	Yes
Power Loss Alarm	Yes
Probe Fault Alarm	Yes
Low Battery Alarm	Yes
Dirty Condenser Alarm	Yes
Evaporator Freezing Alarm	Yes
Acoustic Alarm Silencing Options	Yes
Acoustic Alarm Reactivation	Yes
Alarm Functionality Test	Yes
Calibration	Yes
Alarm Memory	Yes
Door Openings Memory	Yes
Defrost Memory	Yes
Event Memory	Yes
Daily Min/Max Temperature Memory	Yes
Data Logger Function with USB Port	Yes
USB Port	Type B
Data and Event Storage	Yes (on internal memory)
Dry Contact	Yes
Wi-Fi Connectivity	Yes (upon request)
Monitoring App	Yes

## CONTROL PANEL

Backup Battery for Display and Alarms	Yes
Backup Battery Autonomy for Display and Alarms (hours)	48

## ACCESSORIES

Open wire shelf

Chromium plated open wire basket

Stainless steel drawer

Plastic drawer divider

Drawer Perspex front shield

Door key locking

Electronic door lock (available for ADVANCED control panel only)

Temperature chart recorder

Internal electrical socket

Porthole with cover Ø 18 mm

Porthole with cover Ø 45 mm

UVA LED stripe for air sterilization

Glass door

GSM/GPRS telephone dialer

Voltage 230V/1ph/60Hz

Voltage 115V/1ph/60Hz

Plug type A

Plug type B

Plug type G

Plug type I

Wooden crate packing

IQ Documentation

OQ Documentation

## ACCESSORIES

PQ Documentation