



Color: **White**  
Panel: **MINI**

- Structure in white steel plastic coated sheet outside and inside.
- No. 4 feet, fixed, made of plastic material.
- Hinged insulated lid (with counterbalancing hinges), made of the same material and insulation as the rest of the structure, internal counter-lid in non-toxic white plastic material. Perimeter gasket, magnetic type. Lock with key.
- Refrigeration unit in the lower right part of the structure and with condensing unit composed of hermetic compressor and finned condenser, air cooled through a fan. The evaporating pipes are foamed inside the insulating material of all the walls of the storage chamber.
- LED backlit control panel
- Audible and visual alarms

## TECHNICAL FEATURES

Product Code	BDB200
Temperature	-40°C / -60°C
Refrigeration Type	Static
Defrost Type	Manual
Refrigerant Gas	HC
Climatic Class	+16°C / +32°C (N)
Gross Capacity (liters)	125
Net Capacity (liters)	120
External Dimensions (W x D x H mm)	730 x 730 x 925

## ELECTRICAL DATA

Power Supply (V/ph/Hz)	220-230/1/50
Power Plug	Type F
Energy Consumption (kWh/24h)	4,3

## STRUCTURAL FEATURES

Structure	Chest
Insulation Thickness (mm)	100
Counterbalanced Lid	Yes
Heated Door Seal	Yes

## CONTROL PANEL

Display Type	LED
Probe Type	Nr. 1 NTC
Alarm Signaling	Acoustic and visual
Alarm Indications	Codes
Adjustable High/Low Temperature Alarm	Yes
Probe Fault Alarm	Yes
Calibration	Yes

## ACCESSORIES

Basket
One-way rollers Ø 20 mm
Voltage 230V/1ph/60Hz
Plug type G
Plug type I
Wooden crate packing

## ACCESSORIES

[IQ Documentation](#)

[OQ Documentation](#)